

# 175 HP

Engine Model (Color)	(a) E175DSL White (b) E175DGL Graphite (c) E175DPX White (d) E175DGX Graphite (e) E175DCX White
Engine Type	V6 60° E-TEC D.I.
Bore x Stroke - in (mm)	3.601 x 2.588 (91 x 66)
Displacement - cu in (cc) L	158.2 (2592) 2.6L
Gear Ratio	(a)(b) 1.86:1 (c)(d)(e) 1.85:1
Full Throttle RPM Range	5300-6000 RPM
Weight - lbs (kg)*	(a)(b) 418 (190) (c)(d)(e) 433 (19)
Starting	Electric
Controls	Mech. / ICON EST Digital (Acc'y) Mech.
Fuel Induction	E-TEC Direct Injection w/stratified low RPM combustion mode
Alternator Output**	133 Amps Total   50 Net Dedicated
Steering	Remote
Trim Method	FasTrak™ Power Trim and Tilt
Trim Range	-6° to 15°
Tilt Range	75°
Shaft Length - in (mm)	(a)(b) 20 (508) (c)(d)(e) 25 (635)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal	Optional 10, 3, 1.8
Recommended Oil	Evinrude   Johnson XD-100 Oil
Recommended Fuel	87 Octane
Counter Rotation	E175DCX
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013   CARB 3 STAR   European Union



\* Dry weight for the lightest model/version of each engine listed in that grouping.

\*\* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.