## **EVINRUDE**® **E-TEC**® Engine Specifications

## 75 HP

Engine Model (Color)	(a) E75DSL white (b) E75DPGL Graphite
Engine Type	Inline 3-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	3.601 x 2.588 (91 x 66)
Displacement - cu in (cc) L	79.1 (1295) 1.3L
Gear Ratio	2.00:1
Full Throttle RPM Range	5000-5500 RPM
Weight - Ibs (kg)*	320 (145)
Starting	Electric
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection w/stratified low RPM combustion mode
Alternator Output**	81 Amps Total   25 Net Dedicated
Steering	Remote (Tiller Accessory)
Trim Method	Trac-1 Power Trim and Tilt
Trim Range	-4° to 17°
Tilt Range	75°
Shaft Length - in (mm)	20 (508)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	2.4 (2.3)
Recommended Oil	Evinrude   Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013   CARB 3 STAR   European Union



 Dry weight for the lightest model/version of each engine listed in that grouping.
Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

