

9.8 HP

Engine Model (Color)	(a) E10R4 Blue (b) E10RL4 Blue (c) E10TEL4 Blue (d) E10EL4 Blue (e) E10TPL4 Blue (f) E10TPX4 Blue (g) E10PL4 Blue (h) E10PX4B Blue
Engine Type	2-cylinder
Bore x Stroke - in (mm)	55 x 44 (2.17 x 1.73)
Displacement - cu in (cc)	12.8 (209)
Gear Ratio	2.08:1
Full Throttle RPM Range	5000-6000 RPM
Weight - lbs (kg)*	(a)(b) 81.5 (37) (c)(d) 90.4(41) (e) 102.5(46) (f) 104.5(47) (g) 103.6(47) (h) 107(49)
Starting	(a)(b) Rope (c)(d)(e)(f)(g)(h) Electric
Controls	(a)(b) Tiller Handle (c)(d)(e)(f)(g)(h) Mechanical
Fuel Induction	Carbureted
Alternator Output	Only on Electric Models: 12V, 145W, 6A (Standard on Electric Start Models)
Steering	(a)(b)(c)(e)(f) Tiller (d)(g)(h) Remote
Trim Method	Manual or Power Tilt
Shaft Length - in (mm)	(a) 15 (381) (b)(c)(d)(e)(g) 20 (508) (f)(h) 25 (635)
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining



* Dry weight for the lightest model/version of each engine listed in that grouping.

EVINRUDE®

